








Selection Guide

| Series | RTE | GT3A | GT3F |
|---------------------------------|---|---|---|
| Page | 836 | 843 | 851 |
| Appearance |  |  |  |
| Modes of Operation | ON-delay Interval OFF-delay One-shot Cycle (ON first) Cycle (OFF first) Signal OFF delay Signal ON/OFF delay | ON-delay Interval OFF-delay One-shot Cycle (off first) Cycle (on first) Signal OFF delay Signal ON/OFF delay | True Power OFF-delay |
| Time Range | 0.1 second to 600 hrs | 0.1 second to 180 hrs | 0.1 to 600 seconds |
| Contact Configuration | DPDT | SPDT, DPDT | SPDT, DPDT |
| Repeat Accuracy | ±0.25% maximum | ±0.2% maximum | ±0.4% maximum |
| Contact Load Rating (resistive) | 10A, 240V AC | SPDT: 3A, 250V AC DPDT: 5A, 240V AC | 5A, 250V AC |
| Available Operating Voltage | 100-240V AC 12V DC 24V AC/DC | 100 to 240V AC 12V DC 24V AC/DC | 100 to 240V AC 24V AC/DC |
| Approvals | UL Listed c-uL Listed TUV CE | UL Listed c-uL Listed CE | UL Listed c-uL Listed CE |

- 1. For Timing Diagrams Overview, see page 832.
- 2. For all series specific instructions, accessories, and dimensions, see the individual series section.

Switches & Pilot Lights
Signaling Lights
Relays & Sockets
Timers
Contactors
Terminal Blocks
Circuit Breakers

Selection Guide

| Series | GT3W | GE1A | GT5P | GT5Y |
|---------------------------------|---|---|--|---|
| Page | 856 | 866 | 870 | 875 |
| Appearance |  |  |  |  |
| Modes of Operation | Sequential start ON-delay Recycler and instantaneous Recycler OFF start Recycler ON start Interval Interval ON delay Sequential interval | ON-delay | ON-delay | ON-delay |
| Time Range | 0.1s to 300 hrs | 0.1s to 10 hrs | 0.1s to 10 minutes | 0.1s to 1 hour |
| Contact Configuration | DPDT | SPDT, DPDT | SPDT | DPDT, 4PDT |
| Repeat Accuracy | ±0.2% maximum | ±0.2% maximum | ±0.2% maximum | ±0.2% maximum |
| Contact Load Rating (resistive) | 3A, 250V AC 5A, 120V AC/30V DC | 5A, 240V AC | 5A, 250V AC | 5A, DPDT: 250V AC 3A, 4PDT: 250V AC |
| Available Operating Voltage | 100 to 240V AC 12V DC 24V AC/DC | 24V AC/DC 110 to 120V AC 220 to 240V AC | 100 to 120V AC 200 to 240V AC 12V DC 24V DC | 100 to 120V AC 200 to 240V AC 12V DC 24V DC 24V AC |
| Approvals | UL Listed c-uL Listed CE | UL Listed c-uL Listed TUV CE | UL recognized TUV CSA CE | UL Listed c-uL Listed CE |

- 1. For Timing Diagrams Overview, see page 832.
- 2. For all series specific instructions, accessories, and dimensions, see the individual series section.

Switches & Pilot Lights

Signaling Lights

Relays & Sockets

Timers

Contactors

Terminal Blocks

Circuit Breakers